


**CAST 10101852**
**13.5" X 1450'| Cast Hand Film**
**TECHNICAL INFORMATION &  
TYPICAL PROPERTIES**
**>> PRODUCT DESCRIPTION**

This clear, glossy film offers enhanced coverage. Facilitates bar code scanning.

**>> PRODUCT SPECIFICATIONS**
**Film properties**

	<b>TYPICAL VALUE (ENGLISH)</b>	<b>TEST METHOD</b>
Tensile Strength at Yield MD	1 450 psi	ASTM D882
Tensile Strength at Yield TD	1 300 psi	ASTM D882
Tensile Strength at Break MD	5 000 psi	ASTM D882
Tensile Strength at Break TD	3 800 psi	ASTM D882
Elongation at Break MD	320%	ASTM D882
Elongation at Break TD	730%	ASTM D882
Protrusion Puncture	10.0 lbs	ASTM D5748
Protrusion Puncture Energy	19.9 in-lb	ASTM D5748
Elmendorf Tear Strength MD	40 g/mil	ASTM D1922
Elmendorf Tear Strength TD	800 g/mil	ASTM D1922
Cling – Outside to Inside @ 225%	min 150 g/in	ASTM D5458

**Dimensions**

	<b>VALUE</b>
Film Thickness	19 micron