

**EKO EVO I 10200287****500MM x 10 900' | Machine Stretch Film****TECHNICAL INFORMATION &  
TYPICAL PROPERTIES****» PRODUCT DESCRIPTION**

The next generation in high-performance film with up to 250% or more pre-stretch capacity.

**» COLOR**

Clear

**» PRODUCT SPECIFICATIONS****Film properties**

|                            | <b>TYPICAL VALUE<br/>(ENGLISH)</b> | <b>TEST METHOD</b> |
|----------------------------|------------------------------------|--------------------|
| Ultimate Tensile           | 7 270 psi                          | ASTM D882          |
| Ultimate Tensile           | 5 110 psi                          | ASTM D882          |
| Elongation at Break MD     | 652%                               | ASTM D882          |
| Elongation at Break TD     | 774%                               | ASTM D882          |
| Elmendorf Tear Strength MD | 179 g                              | ASTM D1922         |
| Elmendorf Tear Strength TD | 322 g                              | ASTM D1922         |
| Dart Impact Strength       | 178 g                              | ASTM D1709         |
| Gloss @45°                 | 90.0%                              | ASTM D2457         |
| Haze                       | 1.3%                               | ASTM D1003         |

**Dimensions**

|                | <b>VALUE</b> |
|----------------|--------------|
| Film Thickness | 10.4 microns |